

Cross Domain Development Kit | XDK


Start your Sensor X - perience

The universal programmable sensor device & prototyping platform for any IoT use case you can imagine!

Make use of the power to monitor, control and analyze your product remotely over Bluetooth or Wireless Network. In this way, devices, products or machines become connective and smarter. XDK is now released for 24/7 usage giving you the freedom to use it either for short-term proof of concepts or long-term projects. Inclusive of multiple Micro-Electromechanical Systems (MEMS) sensors, various parameters for condition monitoring or predictive maintenance can be recorded.

The **XDK** was designed for rapid prototyping and allows users an easy transition from prototype to mass production by providing a clear road to product development.

BUILT-IN SENSORS



APPLICATION ADVANTAGES

- ▶ All-in-one sensor kit: no need for component selection, hardware assembly, or deployment of a real-time operating system
- ▶ Algorithm library
- ▶ Example code in open source licensing
- ▶ Drivers for all system components included
- ▶ Secure data protocol
- ▶ Small form factor (Length 60 mm x Width 40 mm x Height 22 mm; Weight 54 g)
- ▶ Built-in lithium ion rechargeable battery
- ▶ Functional extendibility via the included extension board
- ▶ High-level API for the standard user and low-level API for the power user
- ▶ CE, FCC, IC, IMDA, ACMA, NTC and NBTC certified | further on request

INCLUDED IN DELIVERY

XDK - Rapid Prototyping Kit

- ▶ XDK Development Kit
- ▶ "XDK Gateway" extension board for easy access to additional MCU functionality
- ▶ 10 cm connector cable
- ▶ Micro USB 2.0 connector cable
- ▶ Mounting plate and screws



MAIN COMPONENTS

- ▶ Bluetooth 4.0 low energy IEEE 802.15.1
- ▶ Wireless LAN IEEE 802.11b/g/n
- ▶ 32-Bit microcontroller (ARM Cortex M3), 1MB Flash, 128 kB RAM
- ▶ Internal Li-Ion rechargeable battery 560 mAh
- ▶ Integrated antennas

OPERATING CONDITIONS

- ▶ Indoor use
- ▶ Operating temperature range -20 °C ... 60 °C, (0 °C ... 45 °C for battery charging)
- ▶ Storage temperature range -20 °C ... 60 °C
- ▶ Humidity range 10...90 %rH (non-condensing)
- ▶ IP Rating IP 30 (IEC 60529)
- ▶ Supply Voltage 5 V DC

MEASUREMENT RANGES

- ▶ Accelerometer $\pm 2 \dots \pm 16$ g (programmable)
- ▶ Gyroscope ± 125 °/s ... ± 2000 °/s (programmable)
- ▶ Magnetic field strength ± 1300 μ T (X,Y-Axis); ± 2500 μ T (Z-Axis)
- ▶ Light sensor 0.045 lux ... 188,000 lux ; 22-bit
- ▶ Temperature -20 °C ... 60 °C [limited by XDK operating conditions]
- ▶ Pressure 300...1100 hPa
- ▶ Humidity 10...90 %rH (non-condensing)
[limited by XDK operating conditions]

SAMPLING RATE

- ▶ Accelerometer BMA280 2000 Hz
- ▶ Gyroscope BMG160 2000 Hz
- ▶ Magnetometer BMM150 300 Hz
- ▶ Hum./Press./Temp. BME280 182 Hz
- ▶ Inertial Measurement Unit
BMI160 1600 Hz (Accelerometer);
3200 Hz (Gyroscope)

SOFTWARE

Free software download for XDK from the website (<https://xdk.io/software-downloads>)

- ▶ Integrated development environment supplied with XDK Workbench (Eclipse)
- ▶ LWM2M communication protocol
- ▶ Extensive libraries and modular source code enable the developer to fully understand the system
- ▶ Datagram Transport Layer Security (DTLS)

USER INTERFACE

- ▶ Power switch
- ▶ Green system LED to display the state of charging
- ▶ 3 programmable status LEDs (red, orange, yellow)
- ▶ 2 programmable push-buttons
- ▶ Micro SD card slot
- ▶ Interface for J-Link Debug-probe
- ▶ Interface for extension board

GET IN CONTACT WITH US

LEGIC Identsystems

E-Mail: info@legic.com

VISIT OUR WEBSITE

www.xdk.io